



**technische import**

**SUCO Productinformatie**

**0194**



SUCO Robert Scheuffele GmbH & Co. KG

**www.bafa.nl**

# M.2

hex 27 integrated

# 0194

Diaphragm pressure switches up to 24 V with gold contacts

- Made of zinc-plated steel (CrVI-free)
- Socket device similar to DIN EN 175301 (DIN 43650)
- Changeover with gold contacts
- Overpressure safety up to 100/300 bar<sup>1)</sup>
- Hysteresis adjustable at factory

$p_{max.}$ in bar	Adjustment range in bar	Tolerance in bar at room temperature	Order number
----------------------	----------------------------	---	--------------

### 0194 Diaphragm pressure switches

100 <sup>1)</sup>	0.3 – 1.5	± 0.2	G 1/4	0194 – 457 03 – X – 003
			M 10x1 con.	0194 – 457 01 – X – 001
			M 12x1.5 cyl.	0194 – 457 02 – X – 002
			NPT 1/8	0194 – 457 04 – X – 318
			NPT 1/4	0194 – 457 09 – X – 314
			7/16-20 UNF	0194 – 457 20 – X – 301
9/16-18 UNF	0194 – 457 21 – X – 302			
300 <sup>1)</sup>	10 – 50	± 3.0	G 1/4	0194 – 458 03 – X – 042
			M 10x1 con.	0194 – 458 01 – X – 040
			M 12x1.5 cyl.	0194 – 458 02 – X – 041
			NPT 1/8	0194 – 458 04 – X – 343
			NPT 1/4	0194 – 458 09 – X – 340
			7/16-20 UNF	0194 – 458 20 – X – 341
9/16-18 UNF	0194 – 458 21 – X – 342			
300 <sup>1)</sup>	10 – 50	± 3.0	G 1/4	0194 – 459 03 – X – 009
			M 10x1 con.	0194 – 459 01 – X – 007
			M 12x1.5 cyl.	0194 – 459 02 – X – 008
			NPT 1/8	0194 – 459 04 – X – 320
			NPT 1/4	0194 – 459 09 – X – 311
			7/16-20 UNF	0194 – 459 20 – X – 305
9/16-18 UNF	0194 – 459 21 – X – 306			
10 – 100	± 3.0 – 5.0	± 3.0 – 5.0	G 1/4	0194 – 461 03 – X – 012
			M 10x1 con.	0194 – 461 01 – X – 010
			M 12x1.5 cyl.	0194 – 461 02 – X – 011
			NPT 1/8	0194 – 461 04 – X – 321
			NPT 1/4	0194 – 461 09 – X – 312
			7/16-20 UNF	0194 – 461 20 – X – 307
9/16-18 UNF	0194 – 461 21 – X – 308			



Socket device included in the delivery



### Seal material – Application areas

<b>NBR</b>	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	<b>1</b>
<b>EPDM</b>	Brake fluid, hydrogen, oxygen, acetylene, etc.	<b>2</b>
<b>FKM</b>	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	<b>3</b>
<b>HNBR</b>	Hydraulic/machine oil, ester-based bio-oils	<b>9</b>

Refer to page 33 for the temperature range and application thresholds of sealing materials.



Your order number:

**0194 – XXX XX – X – XXX**



<sup>1)</sup> Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.



**technische import**

[www.bafa.nl](http://www.bafa.nl)