



**technische import**

# SUCO Productinformatie

# 0171



SUCO Robert Scheuffele GmbH & Co. KG

[www.bafa.nl](http://www.bafa.nl)

# M.4

hex 27

# 0170 / 0171

Diaphragm / piston pressure switches up to 42 V

- Zinc-plated steel (CrVI-free)
- Changeover with silver contacts
- Overpressure safety up to 100/300/600 bar<sup>1)</sup>
- Hysteresis adjustable at factory



$p_{max.}$ in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
----------------------	----------------------------	---	-------------	--------------

### 0170 Diaphragm pressure switches with spade terminal

100 <sup>1)</sup>	0.3 – 1.5	± 0.2	G 1/4	0170 – 457 03 – X – 003
			M 10x1 con.	0170 – 457 01 – X – 001
			M 12x1.5 cyl.	0170 – 457 02 – X – 002
			NPT 1/8	0170 – 457 04 – X – 318
			NPT 1/4	0170 – 457 09 – X – 314
			7/16-20 UNF	0170 – 457 20 – X – 301
9/16-18 UNF	0170 – 457 21 – X – 302			

	1 – 10	± 0.5	G 1/4	0170 – 458 03 – X – 042
			M 10x1 con.	0170 – 458 01 – X – 040
			M 12x1.5 cyl.	0170 – 458 02 – X – 041
			NPT 1/8	0170 – 458 04 – X – 343
			NPT 1/4	0170 – 458 09 – X – 340
			7/16-20 UNF	0170 – 458 20 – X – 341
9/16-18 UNF	0170 – 458 21 – X – 342			

300 <sup>1)</sup>	10 – 50	± 3.0	G 1/4	0170 – 459 03 – X – 009
			M 10x1 con.	0170 – 459 01 – X – 007
			M 12x1.5 cyl.	0170 – 459 02 – X – 008
			NPT 1/8	0170 – 459 04 – X – 320
			NPT 1/4	0170 – 459 09 – X – 316
			7/16-20 UNF	0170 – 459 20 – X – 305
9/16-18 UNF	0170 – 459 21 – X – 306			

	10 – 100	± 3.0 – 5.0	G 1/4	0170 – 461 03 – X – 012
			M 10x1 con.	0170 – 461 01 – X – 010
			M 12x1.5 cyl.	0170 – 461 02 – X – 011
			NPT 1/8	0170 – 461 04 – X – 321
			NPT 1/4	0170 – 461 09 – X – 317
			7/16-20 UNF	0170 – 461 20 – X – 307
9/16-18 UNF	0170 – 461 21 – X – 308			

### 0171 Piston pressure switches with spade terminal

600 <sup>1)</sup>	50 – 200	± 5.0	G 1/4	0171 – 460 03 – X – 003
			M 10x1 con.	0171 – 460 01 – X – 001
			M 12x1.5 cyl.	0171 – 460 02 – X – 002
			NPT 1/8	0171 – 460 04 – X – 304
			NPT 1/4	0171 – 460 09 – X – 303
			7/16-20 UNF	0171 – 460 20 – X – 301
9/16-18 UNF	0171 – 460 21 – X – 302			

### Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
HNBR	Hydraulic/machine oil, ester-based bio-oils	9

Refer to page 53 for the temperature range and application thresholds of sealing materials.



Your order number:

017X – XXX XX – X – XXX



<sup>1)</sup> Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.



**technische import**

[www.bafa.nl](http://www.bafa.nl)