



technische import

SUCO Productinformatie

0190



SUCO Robert Scheuffele GmbH & Co. KG

M.4

hex 27

0190 / 0191

Diaphragm / piston pressure switches up to 24 V with gold contacts

- Zinc-plated steel (CrVI-free), with spade terminal
- Changeover with gold contacts
- Overpressure safety up to 100/300/600 bar¹⁾
- Hysteresis adjustable at factory

p _{max.} in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
-----------------------------	----------------------------	---	-------------	--------------

0190 Diaphragm pressure switches with spade terminal

100 ¹⁾	0.3 – 1.5	± 0.2	G 1/4	0190 – 457 03 – X – 003
			M 10x1 con.	0190 – 457 01 – X – 001
			M 12x1.5 cyl.	0190 – 457 02 – X – 002
			NPT 1/8	0190 – 457 04 – X – 318
			NPT 1/4	0190 – 457 09 – X – 314
			7/16-20 UNF	0190 – 457 20 – X – 301
			9/16-18 UNF	0190 – 457 21 – X – 302

	1 – 10	± 0.5	G 1/4	0190 – 458 03 – X – 042
			M 10x1 con.	0190 – 458 01 – X – 040
			M 12x1.5 cyl.	0190 – 458 02 – X – 041
			NPT 1/8	0190 – 458 04 – X – 343
			NPT 1/4	0190 – 458 09 – X – 340
			7/16-20 UNF	0190 – 458 20 – X – 341
			9/16-18 UNF	0190 – 458 21 – X – 342

300 ¹⁾	10 – 50	± 3.0	G 1/4	0190 – 459 03 – X – 009
			M 10x1 con.	0190 – 459 01 – X – 007
			M 12x1.5 cyl.	0190 – 459 02 – X – 008
			NPT 1/8	0190 – 459 04 – X – 320
			NPT 1/4	0190 – 459 09 – X – 316
			7/16-20 UNF	0190 – 459 20 – X – 305
			9/16-18 UNF	0190 – 459 21 – X – 306

	10 – 100	± 3.0 – 5.0	G 1/4	0190 – 461 03 – X – 012
			M 10x1 con.	0190 – 461 01 – X – 010
			M 12x1.5 cyl.	0190 – 461 02 – X – 011
			NPT 1/8	0190 – 461 04 – X – 321
			NPT 1/4	0190 – 461 09 – X – 317
			7/16-20 UNF	0190 – 461 20 – X – 307
			9/16-18 UNF	0190 – 461 21 – X – 308

0191 Piston pressure switches with spade terminal

600 ¹⁾	50 – 200	± 5.0	G 1/4	0191 – 460 03 – X – 003
			M 10x1 con.	0191 – 460 01 – X – 001
			M 12x1.5 cyl.	0191 – 460 02 – X – 002
			NPT 1/8	0191 – 460 04 – X – 304
			NPT 1/4	0191 – 460 09 – X – 303
			7/16-20 UNF	0191 – 460 20 – X – 301
			9/16-18 UNF	0191 – 460 21 – X – 302

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
HNBR	Hydraulic/machine oil, ester-based bio-oils	9


Refer to page 53 for the temperature range and application thresholds of sealing materials.



Your order number:

019X – XXX XX – X – XXX

¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.





technische import

www.bafa.nl