



**technische import**

**SUCO Productinformatie**

**0241**




SUCO Robert Scheuffele GmbH & Co. KG

[www.bafa.nl](http://www.bafa.nl)

# 0240 / 0241

## Diaphragm / piston pressure switches, hex 27

- Zinc-plated steel (CrVI-free)
- Overpressure safety up to 300 / 600 bar <sup>1)</sup>
- Switching point can also be adjusted during use
- Protection class 2, protective insulation 

p <sub>max.</sub> in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
-----------------------------	----------------------------	---	-------------	--------------

### 0240 Diaphragm pressure switches

p <sub>max.</sub> in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
			G 1/4	0240 - 457 03 - X - 003
300 <sup>1)</sup>	0.3 - 1.5	± 0.2	NPT 1/8	0240 - 457 04 - X - 300
			NPT 1/4	0240 - 457 09 - X - 305
			7/16-20 UNF	0240 - 457 20 - X - 310
			9/16-18 UNF	0240 - 457 21 - X - 315
			G 1/4	0240 - 458 03 - X - 006
1 - 10	± 0.5	± 0.5	NPT 1/8	0240 - 458 04 - X - 301
			NPT 1/4	0240 - 458 09 - X - 306
			7/16-20 UNF	0240 - 458 20 - X - 311
			9/16-18 UNF	0240 - 458 21 - X - 316
			G 1/4	0240 - 459 03 - X - 009
10 - 20	± 1.0	± 1.0	NPT 1/8	0240 - 459 04 - X - 302
			NPT 1/4	0240 - 459 09 - X - 307
			7/16-20 UNF	0240 - 459 20 - X - 312
			9/16-18 UNF	0240 - 459 21 - X - 317
			G 1/4	0240 - 461 03 - X - 012
20 - 50	± 2.0	± 2.0	NPT 1/8	0240 - 461 04 - X - 303
			NPT 1/4	0240 - 461 09 - X - 308
			7/16-20 UNF	0240 - 461 20 - X - 313
			9/16-18 UNF	0240 - 461 21 - X - 318

### 0241 Piston pressure switches

p <sub>max.</sub> in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
			G 1/4	0241 - 460 03 - X - 003
			NPT 1/8	0241 - 460 04 - X - 304
			NPT 1/4	0241 - 460 09 - X - 309
			7/16-20 UNF	0241 - 460 20 - X - 314
9/16-18 UNF	0241 - 460 21 - X - 319			

### Seal material – Application areas


Seal material	Application areas	Order number
NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
HNBR	Hydraulic/machine oil, ester-based bio-oils	9

Refer to page 64 for the temperature range and application thresholds of sealing materials.

Your order number: **024X - XXX XX - X - XXX**

# M.5

hex 24 / 27  
Ready-wired



#### Contact assignment:

- 1 = Black
- 2 = Red
- 4 = White



<sup>1)</sup> Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.



**technische import**

[www.bafa.nl](http://www.bafa.nl)